

Grade	Profile	Dimension		Lenght	Kg
S420MC	angle	66,5	39,5	6.000	2.405
S420MC	angle	66,5	39,5	6.000	2.199
S420MC	angle	66,5	39,5	6.000	2.410
S420MC	angle	66,5	39,5	6.000	2.470
S420MC	angle	66,5	39,5	6.000	2.360
S420MC	angle	66,5	39,5	6.000	2.117
11SMn30	flat	32	44,5	5.800	3.625
11SMn30	flat	32	44,5	5.800	3.810
11SMn30	flat	49	57	6.250	408
C15	flat	40	10	2.800	700
C15	flat	40	10	2.800	840
C35	flat	30	8	2.800	203
C45	flat	20	6	3.150	1.092
C45	flat	20	6	3.130	850
C45	flat	22	72	6.136	3.325
C45	flat	22	72	6.400	3.110
C45	flat	22	72	6.140	4.080
C45	flat	25	8	3.100	484
C45	flat	25	5	3.100	988
C45	flat	25	5	3.100	1.038
C45	flat	30	8	3.150	1.078
C45	flat	30	6	3.100	1.092
C45	flat	32	25	3.150	1.044
C45	flat	35	10	3.140	978
C45	flat	42	32	5.772	2.064
C45	flat	42	102	3.000	204
C45	flat	45	8	3.100	1.024
C45	flat	45	8	3.100	1.024
C45	flat	100	8	3.100	392
C45	flat	100	8	3.100	536
C45	flat	145	20	3.200	732
C45E	flat	18	17	6.330	816
C45E	flat	41	50	6.790	1.282
C45R	flat	8	35	4.070	464
C45R	flat	8	35	3.900	878
C45R	flat	8	38	4.200	2.198
C45R	flat	9	35	3.400	964
Ck45	flat	42	32	5.772	3.340
S235JR	flat	35	9	3.200	885
S235JRC	flat	27	131	8.740	3.946
S235JRC	flat	37	52	6.408	2.527
S235JRC	flat	37	52	6.385	2.430
S235JRC	flat	62	102	4.052	2.680
S235JRC	flat	62	102	4.052	2.680
SAE1018	flat	33,5	52	7.000	4.745
SAE1018	flat	33,5	52	7.000	4.855
SAE1018	flat	116	58,5	7.050	1.468
SAE1018	flat	116	58,5	7.050	4.395
SAE1018	flat	116	58,5	3.525	1.651

various	flat	55	100	9.000	777
various	flat			3.300	405
					<hr/>
					92.068